

---

## FLOODLIGHT LED 10 W 4000 K WT

LEDVANCE FLOODLIGHT LED | LED floodlight luminaires



---

### Areas of application

- Replacement for floodlights with halogen lamps
- Car parks and underpasses
- Garages
- Public areas
- Building facades
- Construction areas

---

### Product benefits

- Energy savings of up to 90 % compared to halogen lamp floodlights
- Optimized weight and size due to compact design
- Very homogenous light

---

### Product features

- Luminaire efficacy: up to 100 lm/W
- Beam angle: 100°
- Type of protection: IP65
- Certificates: CE, CB, TUEV SUED



## Technical data

### Electrical data

Operating mode	Electronic control gear (EVG)
Nominal wattage	10.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

### Photometrical data

Color temperature	4000 K
Luminous flux	800 lm
Light color (designation)	Cool White
Color rendering index Ra	≥80

### Light technical data

Beam angle	100.00 °
------------	----------

### Dimensions & weight

Length	117.0 mm
Width	127.0 mm
Height	39.0 mm

### Colors & materials

Body material	Polycarbonate (PC)
Product color	White

### Temperatures & operating conditions

Ambient temperature range	-20...50 °C
---------------------------	-------------

### Lifespan

Lifespan	30000 h
----------	---------

### Capabilities

Dimmable	No
Type of connection	Cable, 3-pole

### Certificates & standards

Protection class	I
Type of protection	IP65

## Product datasheet

<b>Standards</b>	CE/CB/TÜV SÜD/EAC/ROHS
<b>Energy efficiency class</b>	A

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075810952	FLOODLIGHT LED 10 W 4000 K WT	Shipping carton box 10	280 mm x 248 mm x 210 mm	14.58 dm <sup>3</sup>	5.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.